



AVANTI

Stop leaks. Stabilize soil.
Control groundwater. **Permanently.**

Rev 11.2018

TECHNICAL DATA SHEET

AV-208 TECHNICAL GRADE ACETONE™

MOISTURE REMOVING AGENT

DESCRIPTION

Avanti's **AV-208** Technical Grade Acetone is used for removing all moisture in the grouting equipment.

PACKAGING

5 Gallon Container Net Wt. 38 lbs. (17.2 kg)

SHIPPING

- Motor Class 77.5
- Hazard Class 3 (Flammable)
- Air freight available for pails ONLY



PROPERTIES*

Appearance:	Clear liquid
Flash Point:	1.4°F (-17°C)
Melting Point:	-137°F (-94°C)
Boiling Point:	129°F (54°C)
Autoignition Temp:	N/A
Lower Flammable Limit:	2% (in air)
Upper Flammable Limit:	13% (in air)
Evaporation Rate:	>1
Percent Volatile:	100% (by volume)
Vapor Pressure:	184 mm Hg @ 68°F (20°C)
Vapor Density:	2.0 (air=1)
Specific Gravity:	0.786
Solubility in Water:	Soluble

*Laboratory Results

HOW IT WORKS

It is important to pump Avanti's **AV-208** through the grouting equipment prior to grouting as it removes moisture. Avanti grouts are water sensitive; therefore moisture removal is vital to successful grouting operations.

STORAGE

Store in temperatures within or near 45°F – 95°F (7°C – 35°C) in a tightly closed container in a cool, ventilated, dry atmosphere. Keep away from heat and ignition sources.

SAFETY

Always use OSHA-approved personal protective equipment (PPE). Refer to the SDS for complete safety precautions. The SDS is available by request or via download at avantigrout.com.

NOTICE

The data, information and statements contained herein are believed to be reliable, but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. **NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE.** In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.