

AV-249 HV Flexseal CAT HV™**SECTION 1. IDENTIFICATION**

Product Identifier	AV-249 HV Flexseal CAT HV
Other Means of Identification	Catalyst for hydrophobic grout
Recommended Use	Industrial Use Only.
Restrictions on Use	Not applicable.
Manufacturer/Supplier Identifier	Avanti International, 822 Bay Star Blvd, Webster, TX, 77598, USA, 281.486.5600, avantigrout.com
Emergency Phone No.	ChemTrec, 800.424.9300
Date of Preparation	April 03, 2018

SECTION 2. HAZARD IDENTIFICATION

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015) and the US Hazard Communication Standard (HCS 2012).

Classification

Acute toxicity (Oral) - Category 4; Skin irritation - Category 2; Eye irritation - Category 2A; Skin sensitization - Category 1; Specific target organ toxicity (repeated exposure) - Category 2

Label Elements

Signal Word:

Warning

Hazard Statement(s):

H302 + H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs (kidneys) through prolonged or repeated exposure if inhaled and/or swallowed.

Precautionary Statement(s):

Prevention:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands and skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear eye protection/face protection.

P280 Wear protective gloves.

P273 Avoid release to the environment.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water/

Product Identifier: AV-249 HV Flexseal CAT HV - Ver. 1

Date of Preparation: April 03, 2018

Date of Last Revision: May 12, 2018

Page 01 of 07

Soap
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice or attention if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice or attention.

P337 + P313 If eye irritation persists: Get medical advice or attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

Other Hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Amines, coco alkyl	61788-46-3	50	Amine	
Dibutyl maleate	105-76-0	30	DBM	
Octamethylcyclotetrasiloxane	556-67-2	1	Silicone	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Get medical advice or attention if you feel unwell.

Skin Contact

Immediately wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 15-20 minutes. If skin irritation or a rash occurs, get medical advice or attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Get medical advice or attention if you feel unwell or are concerned.

First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled and/or swallowed: can cause effects as described for inhalation. Can cause effects as described for skin contact.

Immediate Medical Attention and Special Treatment

Target Organs

Kidneys, respiratory system.

Special Instructions

Monitor kidney function. Monitor cardiovascular function.

Medical Conditions Aggravated by Exposure

Asthma, dermatitis, kidney conditions, respiratory conditions.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Product Identifier: AV-249 HV Flexseal CAT HV - Ver. 1

Date of Preparation: April 03, 2018

Date of Last Revision: May 12, 2018

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Unsuitable Extinguishing Media

DO NOT use water or water-based extinguishing agents.

Specific Hazards Arising from the Product

Closed containers may rupture violently when heated releasing contents.

Very toxic carbon monoxide, carbon dioxide; corrosive, oxidizing nitrogen oxides.

Special Protective Equipment and Precautions for Fire-fighters

Approach fire from upwind to avoid hazardous vapours or gases. Do NOT apply water directly to spill.

Chemical protective clothing (e.g. chemical splash suit) and positive pressure SCBA may be necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Increase ventilation to area or move leaking container to a well-ventilated and secure area. Remove or isolate incompatible materials as well as other hazardous materials.

Environmental Precautions

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product. Place used absorbent into suitable, covered, labelled containers for disposal. Contaminated absorbent poses the same hazard as the spilled product. Dike spilled product to prevent runoff. Remove or recover liquid using pumps or vacuum equipment. Store recovered product in suitable containers that are: tightly-covered.

Other Information

Contact supplier, local fire and emergency services for help.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not breathe in this product. Prevent skin contact. Do not get in eyes. Do not swallow. Avoid exposure during pregnancy and while nursing. Avoid generating vapours or mists. Avoid heating that will increase the amount of vapours. Wear personal protective equipment to avoid direct contact with this chemical. Keep containers tightly closed when not in use or empty. General hygiene considerations: do NOT smoke in work areas. Do NOT eat, drink or store food in work areas. Remove contaminated clothing and protective equipment before entering eating areas or leaving work area. Consider using a double locker-shower facility. Wash hands thoroughly after handling this product and before eating, using the washroom or leaving work area. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely. Properly dispose of any contaminated items, including shoes, that cannot be decontaminated. DO NOT re-use.

Conditions for Safe Storage

Store in an area that is: cool, well-ventilated.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Not available.

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Provide eyewash and safety shower if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

Product Identifier: AV-249 HV Flexseal CAT HV - Ver. 1

Date of Preparation: April 03, 2018

Date of Last Revision: May 12, 2018

Page 03 of 07

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots. Wear a chemical splash suit and respiratory protection.

Suitable materials are: Chemical Resistant Gloves: butyl rubber, neoprene rubber, nitrile rubber, polyvinyl chloride, Viton®/butyl rubber. Chemical Resistant Suit: Barrier® (PE/PA/PE), Saranex®.

Respiratory Protection

Wear a NIOSH approved air-purifying respirator with an organic vapour cartridge. Either full-face piece or half-face piece with splash goggles.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear yellow liquid.
Odour	Pungent
Odour Threshold	Not available
pH	Not available
Melting Point/Freezing Point	Not available (melting); < 54 °F (12 °C) (freezing)
Initial Boiling Point/Range	Not available
Flash Point	> 242.6 °F (117.0 °C)
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.94
Solubility	Slightly soluble in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)
Other Information	
Physical State	Liquid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

None known.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

Reacts violently in the presence of acidic conditions (low pH).

Conditions to Avoid

Sunlight. Incompatible materials. Acidic conditions (low pH).

Incompatible Materials

Reacts violently with: organic acids (e.g. acetic acid), inorganic acids (e.g. hydrofluoric acid), oxidizing agents (e.g. peroxides), strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid).

Hazardous Decomposition Products

Product Identifier: AV-249 HV Flexseal CAT HV - Ver. 1

Date of Preparation: April 03, 2018

Date of Last Revision: May 12, 2018

Very toxic carbon monoxide, carbon dioxide; corrosive, oxidizing nitrogen oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Dibutyl maleate		9300 mg/kg (mouse)	10010 mg/kg (rabbit)
Amines, coco alkyl		740 mg/kg (rat)	

Skin Corrosion/Irritation

May cause moderate or severe irritation based on information for closely related materials.

Serious Eye Damage/Irritation

May cause serious eye irritation based on information for closely related materials.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May be harmful based on information for closely related materials.

Skin Absorption

May be harmful based on information for closely related materials.

Ingestion

May be harmful based on information for closely related materials.

Aspiration Hazard

No information was located.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause harmful effects on the kidneys. Symptoms may include dry, red, cracked skin (dermatitis). Irritation of the respiratory system. May cause respiratory tract injury.

Respiratory and/or Skin Sensitization

Respiratory sensitizer. Skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Dibutyl maleate	Not Listed	Not Listed	Not Listed	Not Listed

No information was located.

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

May cause effects on sexual function and/or fertility.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

No information was located.

Product Identifier: AV-249 HV Flexseal CAT HV - Ver. 1

Date of Preparation: April 03, 2018

Date of Last Revision: May 12, 2018

Page 05 of 07

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Dibutyl maleate	0.6 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour)	21 mg/L (Daphnia magna (water flea); 48-hour)	6.2 mg/L (Desmodesmus subspicatus (algae); 72-hour)	
Amines, coco alkyl	0.1-1 mg/L (96-hour; semi-static)			

Persistence and Degradability

No information was located.

Bioaccumulative Potential

This product or its degradation products are expected to bioaccumulate.

Mobility in Soil

If released into the environment, this product is not expected to move through the soil, based on physical and chemical properties.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations. Dispose of or recycle empty containers through an approved waste management facility. Empty containers retain product residue. Follow label warnings even if container appears to be empty. Do not reuse empty containers.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

Environmental Hazards Not applicable

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Product Identifier: AV-249 HV Flexseal CAT HV - Ver. 1

Date of Preparation: April 03, 2018

Date of Last Revision: May 12, 2018

SECTION 16. OTHER INFORMATION

NFPA Rating **Health - 2** **Flammability - 1** **Instability - 1**

SDS Prepared By Avanti International

Date of Preparation April 03, 2018

Date of Last Revision May 12, 2018

Revision Indicators Not applicable.

Key to Abbreviations ACGIH® = American Conference of Governmental Industrial Hygienists
IARC = International Agency for Research on Cancer
NFPA = National Fire Protection Association NIOSH = National Institute for Occupational Safety and Health
NTP = National Toxicology Program
OSHA = US Occupational Safety and Health Administration
RTECS® = Registry of Toxic Effects of Chemical Substances

References CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).
HSDB® database. US National Library of Medicine. Available from Canadian Centre for Occupational Health and Safety (CCOHS). NIOSH Pocket Guide database. National Institute for Occupational Safety and Health. Available from Canadian Centre for Occupational Health and Safety (CCOHS). Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault Systèmes/BIOVIA ("BIOVIA"). Available from Canadian Centre for Occupational Health and Safety (CCOHS).

Product Identifier: AV-249 HV Flexseal CAT HV - Ver. 1

Date of Preparation: April 03, 2018

Date of Last Revision: May 12, 2018

Page 07 of 07