

Mechanical Injector/Packer Resin Injector



Description

The 3" mechanical injectors/packers are available in 1/2" (red) and 5/8" (blue) outside diameters and are reusable. These injectors/packers are designed for both 45 degree and straight-on injection of cracks and expansion joints. Both the 1/2" and 5/8" packers have 0.375" diameter port for injection of large volumes of material. Tolerant of pressure fluctuations. May be used with injector extension. Rubber sleeve color may differ.

Applications

- Zerk fitting tips allow for low to high pressure injection.
- Typically used for either crack injection or curtain grouting techniques such as the Variable Pressure Application Technique (VPAT) and the Curtain Grouting Application Technique (CGAT).

Packaging

- Injectors sold individually

Safety

Always use OSHA-approved personal protective equipment (PPE).

Shipping – Motor and Air Freight available

- Motor Class 55
- Non-Hazardous
- Air freight available

Notice

The data, information and statements contained herein are believed to be reliable but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE. In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.