

TECHNICAL DATA SHEET

AV-105 GEL GUARD™

FREEZING POINT REDUCER

DESCRIPTION

AV-105 Gel Guard is designed to reduce the freezing point of Avanti's chemically activated and hydrophilic urethane gel systems.

APPLICATION

- Use as a freezing point reducer for cold weather applications

FEATURES AND BENEFITS

- Adding 10% can lower freezing temperatures by as much as 9°F/5°C
- Easily added to chemical grout solution

HOW IT WORKS

AV-105 may be added to each side/tank of the chemically activated gel systems or water side/tank only for hydrophilic urethane gel systems. Refer to the technical data sheet for information on a specific Avanti International gel system.

ADDITIVE FOR

- **AV-100**® Chemical Grout
- **AV-118**® Duriflex
- **AV-254** Gelseal™ (add to water-side only)
- **AV-350** Multigel™ (add to water-side only)

PACKAGING

Product packaged by weight:
Net Wt.

Pail	46 lbs. (20.8 kg)
Drum	510 lbs. (231.3 kg)

SHIPPING

- Motor Class 65
- Non-Hazardous
- Air freight available

PROPERTIES*

Appearance:	Clear liquid
Viscosity:	15 – 20 cP @ 72°F (22°C)
Flash Point:	>200°F (>93°C)
Specific Gravity:	1.115 @ 72°F (22°C) ± 3%
Weight:	9.28 lbs./gal ± 3% (1.119 kg/L ± 3%)

*Laboratory Results

MIX PROCEDURE

If mixing with **AV-100** or **AV-118**, add up to 2.7 gallons (10.2 L) to both the grout side/tank and the catalyst side/tank for a 10% **AV-105** concentration. If mixing with **AV-254** or **AV-350**, add 10% of the volume of the water being used to water side/tank only. Applying chemistries in temperatures below 40°F (5°C) is not recommended. Refer to the product Technical Manual to see mixing instructions for specific gel product.

CLEANING PRODUCTS

Use water with light detergent.

STORAGE

Store in a tightly closed container in a cool, ventilated, dry atmosphere.

SAFETY

Always use OSHA-approved personal protective equipment (PPE). Refer to the SDS for complete safety precautions. The SDS is available by request or via download at avantigrout.com.

NOTICE

The data, information and statements contained herein are believed to be reliable, but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. **NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE.** In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.

Freezing Point			
AV-105 Concentration	10%	20%	30%
20% AV-100 mixed with 2%AV-101	12°F (-11°C)	-3°F (-19°C)	-26°F (-32°C)
2% AV-102 Solution	19°F (-7°C)	10°F (-12°C)	-5°F (-20°C)
Water	26°F (-3°C)	18°F (-8°C)	7°F (-14°C)