

TECHNICAL DATA SHEET

AV-222 CLEANER™

CURED GROUT REMOVING AGENT

DESCRIPTION

AV-222 Cleaner dissolves cured polyurethane resin from the grouting equipment.

PACKAGING

Pail 5 Gallon (19 L)

SHIPPING

- Motor Class 77.5
- Hazard Class 3 (Flammable) / Hazard Class 8 (Corrosive)
- Air freight NOT available



CLEANING PRODUCTS

- **AV-208** Technical Grade Acetone™ (CAS# 67-64-1) – removes moisture from grouting equipment
- **AV-284** Pump Wash™ (Proprietary Blend) – removes uncured resin from grouting equipment. Also, can be stored in grouting equipment for extended periods when pump is not in use.

PROPERTIES*

| | |
|-----------------|--------------------------------|
| Appearance: | Light Yellow |
| Viscosity: | 3 cP @ 70°F (21°C) |
| Flash Point: | 58°F (14°C) |
| pH: | 12.3 +/- 0.2 |
| Solids Content: | 3% +/- 0.2% |
| Weight: | 7.0 lbs. per gal. +/- 0.1 lbs. |

*Laboratory Results

HOW IT WORKS

If the grouting equipment is clogged with cured resin, the procedure below may be followed:

1. Disassemble clogged pieces and soak in **AV-222** Cleaner overnight.
2. After soaking overnight, rinse the parts with water to remove remaining **AV-222** solution.
3. Remove dissolved cured resin from the parts using air pressure.
4. Once cured resin is removed, assemble pieces.
5. Flush all grouting equipment with **AV-284** Pump Wash to completely flush any residual chemical grout.

STORAGE

Store in a tightly closed container in a cool, ventilated, dry atmosphere. Keep away from heat and ignition sources.

SAFETY

Always use OSHA-approved personal protective equipment (PPE). Refer to the SDS for complete safety precautions. The SDS is available by request or via download at avantigrout.com.

NOTICE

The data, information and statements contained herein are believed to be reliable, but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. **NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE.** In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.